

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>A23D 7/00</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 97/43907</b> <b>(43) International Publication Date:</b> 27 November 1997 (27.11.97)
<b>(21) International Application Number:</b> PCT/US97/09326 <b>(22) International Filing Date:</b> 21 May 1997 (21.05.97) <b>(30) Priority Data:</b> 08/651,684 21 May 1996 (21.05.96) US <b>(60) Parent Application or Grant</b> <b>(63) Related by Continuation</b> US 08/651,684 (CIP) Filed on 21 May 1996 (21.05.96) <b>(71) Applicant (for all designated States except US):</b> CARGILL, INCORPORATED [US/US]; 15407 West McGinty Road, Wayzata, MN 55391 (US). <b>(72) Inventors; and</b> <b>(75) Inventors/Applicants (for US only):</b> DHARMA, R., Kodali [IN/US]; 710 Olive Lane North, Plymouth, MN 55447 (US). ZHEGONG, Fan [CN/US]; 4429 Monte Carlo Place, Fort Collins, CO 80525 (US). <b>(74) Agent:</b> LUNDQUIST, Ronald, C.; Fish & Richardson P.C., P.A., Suite 3300, 60 South Sixth Street, Minneapolis, MN 55402 (US).		<b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i>
<b>(54) Title:</b> HIGH STABILITY CANOLA OILS  <b>(57) Abstract</b>  Hydrogenated canola oils having improved oxidative stability are disclosed. These oils have relatively low levels of <i>trans</i> -fatty acids and saturated fatty acids, yet possess an oxidative stability of greater than 300 AOM hours. Such oils can be produced by hydrogenation of refined, bleached canola oil extracted from <i>Brassicaceae</i> seeds having elevated levels of oleic acid and reduced levels of polyunsaturated fatty acids. <i>Brassica</i> lines producing seeds having such fatty acid profiles are disclosed. Hydrogenated oils may be fractionated to obtain canola oils that are liquid at or below room temperature and have relatively low levels of <i>trans</i> -fatty acids and saturated fatty acids, yet have an oxidative stability of greater than 300 AOM hours.		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KR	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

- 1 -

HIGH STABILITY CANOLA OILSField of the Invention

The present invention relates to hydrogenated  
5 canola oil having improved oxidative stability and  
performance attributes, and to *Brassica* seeds, plant  
lines and progeny thereof from which such an oil is  
derived.

Background of the Invention

10 Canola oil has the lowest level of saturated fatty  
acids of all vegetable oils. As consumers become more  
aware of the health impact of lipid nutrition,  
consumption of canola oil in the U.S. has increased.  
However, canola oil extracted from many natural and  
15 commercial varieties of rapeseed contains a relatively  
high  $\alpha$ -linolenic acid content ( $C_{18:3}$ ; all cis 9,12,15  
octadecatrienoic acid; ALA). The oil is unstable and  
easily oxidized during cooking, which in turn creates  
off-flavors and compromises the sensory characteristics  
20 of foods cooked in such oils. It also develops  
unacceptable off odors and rancid flavors during storage.

Hydrogenation can be used to improve performance  
attributes by lowering the amount of linoleic and  $\alpha$ -  
linolenic acids in the oil. Hydrogenation converts cis  
25 mono- and cis poly-unsaturated fatty acids into trans-  
fatty acids and saturated fatty acids. Saturated and  
trans-fatty acids are not desirable for health reasons.  
It would be desirable to reduce the level of  
polyunsaturates in order to improve the oxidative  
30 stability and the shelf life of these oils while  
minimizing the increase in trans-fatty acids and  
saturated fatty acids.

- 2 -

Different vegetable oils can be blended to reduce the  $\alpha$ -linolenic acid content and improve performance attributes. However, blending canola oil with other vegetable oils such as cottonseed oil increases the  
5 saturated fatty acid content of the final product and decreases the healthy attributes of canola oil.

$\alpha$ -Linolenic acid has been reported to have a relatively low oxidative stability. In general, the oxidative stability of oleic acid is about 10 fold  
10 greater than that of linoleic acid, and the oxidative stability of linoleic acid is about 2 fold greater than that of linolenic acid.

Linoleic and  $\alpha$ -linolenic acids have been suggested as precursors to undesirable odor and flavor development  
15 in foods. To improve the functionality of canola oil, the University of Manitoba developed the canola variety "Stellar" which has reduced  $\alpha$ -linolenic acid (Scarth et al., Can. J. Plant Sci., 68:509-511 (1988)). The low  $\alpha$ -linolenic acid oil was reduced in odor when heated in  
20 air, but still remained unacceptable to the sensory panel in flavor evaluations (Eskin et al., J. Am. Oil Chem. Soc. 66:1081-1084 (1989)). The oxidative stability of Stellar oil increased by 17.5% over the commercial variety Westar as measured by Active Oxygen Method (AOM)  
25 hours. (Can. J. Plant Sci. (1988) Vol. 68, pp. 509-511).

European Patent Application, EP 0 323 753 A1 describes a canola oil having an enhanced oleic acid content and suggests that such an oil would have increased heat stability in combination with other  
30 traits. The application describes a canola oil with reduced  $\alpha$ -linolenic acid. However, no flavor or performance testing was reported for any oil.

The factors affecting oxidative stability and flavor stability of canola oils are not completely  
35 understood, although it is known that the amount of  $\alpha$ -

- 3 -

linolenic acid in the oil affects oxidative stability and flavor stability. A canola oil is needed that possesses very high oxidative stability and improved flavor and odor characteristics.

5

Summary of the Invention

Hydrogenated canola oils are disclosed herein. In one aspect of the invention, an oil has a Mettler Drop Point (MDP) of more than about 30°C, a trans-fatty acid content of about 36% or less, an IV of from about 68 to  
10 about 75 and a minimum AOM value of about 280 hours in the absence of added antioxidants. In some embodiments, this oil is produced from a starting oil extracted from Brassicaceae seeds that have a fatty acid profile comprising an oleic acid content of about 72% to about  
15 80%, a linoleic acid content of about 5% to about 12% and an  $\alpha$ -linolenic acid content of about 1% to about 5%. The fatty acid profile in such seeds may be controlled by heritable genetic change that is present in seeds designated as IMC-130 and deposited as ATCC accession  
20 number 75446.

The hydrogenated oil can be separated to obtain a liquid oil fraction that has an MDP of less than about 20°C, a trans-fatty acid content of about 31% or less, an IV of from about 72 to about 77 and a minimum AOM value  
25 of about 290 hours in the absence of added antioxidants. In some embodiments, the liquid oil fraction can have a minimum AOM value about 330 hours.

In another aspect of the invention, a hydrogenated canola oil has an MDP of more than about 30°C, a trans-  
30 fatty acid content of about 40% or less, an IV of from about 68 to about 77, a total C18:1 content of about 80% or greater and a minimum AOM value of about 300 hours in the absence of

- 4 -

added antioxidants. If desired, the hydrogenated oil can be separated to obtain a liquid oil fraction that has an MDP of less than about 20°C, a trans-fatty acid content of about 40% or less, an IV of from about 75 to about 81, 5 a total C18:1 fatty acid content of about 86% or greater and a minimum AOM value of about 350 hours in the absence of added antioxidants. Such an oil may have a total saturated fatty acid content of less than about 9.5%.

In some embodiments, such an oil is produced from 10 a starting oil extracted from *Brassicaceae* seeds having a fatty acid profile comprising an oleic acid content of about 80% to about 87%, a linoleic acid content of about 2% to about 5% and an  $\alpha$ -linolenic acid content of about 1% to about 4%. Such seeds can possess defects in both 15 the first and second forms of delta-12 fatty acid desaturase found in *Brassicaceae* lines. The fatty acid profile may be controlled by heritable genetic change in a line designated 6Q4275A-1-4 and having ATCC accession number 97569.

20 A method of producing a canola oil is disclosed herein. In one embodiment, the method comprises the steps of providing a starting refined, bleached non-hydrogenated canola oil that has an oleic acid content of from about 72% to about 80%, a linoleic acid content of 25 from about 5% to about 12% and an  $\alpha$ -linolenic acid content of from about 1% to about 5%; and hydrogenating the starting oil to an IV of from about 68 to about 75. The hydrogenated oil has an MDP of more than about 30°C, a trans-fatty acid content of about 36% or less and a 30 minimum AOM value of about 280 hours in the absence of added antioxidants. The method may further comprise the step of separating the hydrogenated oil into a solid fraction and a liquid canola oil fraction. The liquid fraction has an MDP of less than about 20°C, a trans- 35 fatty acid content of less than about 31%, an IV of from

- 5 -

about 72 to about 77 and a minimum AOM value of about 290 hours in the absence of added antioxidants. The starting oil may be extracted from *Brassicaceae* seeds designated IMC-130 and having ATCC accession number 75446.

5 Another method of producing a canola oil comprises the steps of providing a starting refined, bleached non-hydrogenated canola oil that has an oleic acid content of from about 80% to about 87%, a linoleic acid content of from about 2% to about 5% and an  $\alpha$ -linolenic acid content  
10 of from about 1% to about 4%; and hydrogenating the starting oil to an IV of from about 68 to about 77. The hydrogenated oil has an MDP of more than about 30°C, a trans-fatty acid content of about 40% or less and a minimum AOM value of about 300 hours in the absence of  
15 added antioxidants. The method may further comprise the step of separating the hydrogenated oil into a solid fraction and a liquid canola oil fraction. The liquid fraction has an MDP of less than about 20°C, a trans-fatty acid content of about 40% or less, an IV of from  
20 about 75 to about 81, a total C18:1 fatty acid content of greater than about 85% or greater and a minimum AOM value of about 350 hours in the absence of added antioxidants. The starting oil may be extracted from *Brassicaceae* seeds having defects in both the first and second forms of  
25 delta-12 fatty acid desaturase. The starting oil may be extracted from *Brassicaceae* seeds designated 6Q4275A-1-4 and having ATCC accession number 97569.

#### Detailed Description of the Invention

The present invention provides a hydrogenated  
30 canola oil that is low in saturated fatty acids and low in trans- fatty acids. The oil has superior oxidative stability, sensory characteristics and frying attributes when compared to known canola oils. In some embodiments, the modified oil is liquid at or below room temperature.

- 6 -

In the context of this disclosure, total saturated fatty acids include myristic (C14:0), palmitic (C16:0), stearic (C18:0), arachidic (C20:0), behenic (C22:0), and lignoceric (C24:0) acids. Trans-fatty acids include any trans isomer of a C<sub>14</sub> through C<sub>24</sub> fatty acid. Total C18:1 fatty acid refers to isomers of C18 monounsaturated fatty acids. Total C18:2 fatty acid refers to isomers of C18 diunsaturated fatty acids. Total C18:3 fatty acids refers to isomers of C18 triunsaturated fatty acids.

As used herein, "functionality" or "performance attributes" means properties or characteristics of the canola oil and includes flavor stability, fry stability, and oxidative stability.

"Oxidative stability" relates to how easily components of an oil oxidize, and can be measured, for example, by instrumental analyses such as Active Oxygen Method (AOM) American Oil Chemists' Society Official Method Cd 12-57 for Fat Stability:Active Oxygen Method (rev'd 1989); Rancimat (Laubli, M.W. and Bruttel, P.A., JOACS 63:792-795 (1986)) and Oil Stability Index (OSI) values, AOCS Method Cd 12b-92.

"Canola" refers to rapeseed (*Brassica*) that has an erucic acid (C<sub>22:1</sub>) content of at most 2 percent by weight based on the total fatty acid content of a seed, preferably at most 0.5 percent by weight and most preferably essentially 0 percent by weight and that produces, after crushing, an air-dried meal containing less than 30 micromoles ( $\mu\text{mol}$ ) of glucosinolates per gram of defatted (oil-free) meal.

A starting canola oil for use in the invention typically has been refined and bleached by methods known in the art. The starting refined, bleached (RB) canola oil may be further processed before hydrogenation, provided that such processing does not interfere with the subsequent hydrogenation process.



- 7 -

A starting canola oil preferably is derived from seeds having a low total glucosinolate content. Under standard processing conditions, an RB oil derived from seeds having a low total glucosinolate content generally  
5 has a lower sulfur content, compared to an RB oil derived from seeds having a high total glucosinolate content. Brassicaceae lines producing seeds having a low total glucosinolate content are described in U.S. Application Serial No. 08/290,660, incorporated herein by reference.  
10 The sulfur content of the starting oil is generally less than about 3.8 ppm, preferably less than about 3.0 ppm. In preferred embodiments, the oil has a sulfur content of less than about 1.5 ppm.

In one embodiment, an oil of the invention is  
15 hydrogenated such that the oil has a Mettler Drop Point (MDP) of from about 30°C to about 45°C, preferably less than about 40°C, more preferably less than about 35°C. The iodine value (IV) is about 68 to about 75, preferably from about 70 to about 73.

20 Such an oil possesses a relatively low trans-fatty acid content of less than about 36% wt. %. In preferred embodiments the trans-fatty acid content is less than about 31%, preferably less than about 27%, more preferably less than about 25%. The stearic acid content  
25 of an oil of this embodiment typically is from about 10% to about 15%, preferably from about 10% to about 12%. The total saturated fatty acid content is from about 10% to about 20%, preferably from about 13% to about 18%. In addition, the total C18:1 fatty acid content of such an  
30 oil is greater than about 75%, preferably greater than about 80%.

Such an oil has a high oxidative stability. When oxidative stability is measured by the active oxygen method (AOM), the AOM value is from about 280 hours to  
35 about 350 hours, preferably from about 300 hours to about

- 8 -

350 hours. In preferred embodiments, the AOM value is from about 325 hours to about 350 hours.

In a second embodiment, a starting canola oil is hydrogenated and fractionated to obtain an oil that is liquid at or below room temperature. For example, such an oil has a MDP of less than about 20°C, preferably less than about 18°C.

An oil of the second embodiment possesses a low trans-fatty acid content of from about 20% to about 33%, preferably from about 23% to about 26%. An oil of this embodiment also possesses a low saturated fatty acid content. The stearic acid content typically is from about 7.5% to about 9.5%. The total saturated fatty acid content is from about 10% to about 14%, preferably from about 11% to about 12%. An oil of this embodiment possesses a total C18:1 fatty acid content of about 79% to about 87%, preferably from about 81% to about 83%. The IV is from about 72 to about 77, preferably from about 73 to about 76.

Such an oil has a high oxidative stability (measured in AOM hours) of about 290 hours to about 375 hours, preferably from about 330 hours to about 360 hours, more preferably from about 330 hours to about 350 hours.

An oil of these embodiments can be produced, for example, by hydrogenation of a starting canola oil extracted from *Brassica* seeds having a fatty acid profile comprising an oleic acid content of about 72% to about 80%, a linoleic acid content of about 5% to about 12% and an  $\alpha$ -linolenic acid content of about 1% to less than about 5%.

Seeds having the indicated fatty acid profile are produced, for example, by canola lines IMC-130 (ATCC Accession No. 75446) and A13.30137, disclosed in U.S.

- 9 -

Patent Application 08/425,108, filed June 6, 1995, which is incorporated herein by reference.

Progeny of crosses between a first *Brassica* line (such as IMC-130) and an agronomically elite line are  
5 also suitable for producing such a starting canola oil, provided that the progeny possess the fatty acid profile of the first *Brassica* line and that the starting oil derived from the progeny can be hydrogenated as disclosed herein. Plant breeding techniques for producing such  
10 progeny are known in the art.

In a third embodiment, starting canola oil has been hydrogenated such that the oil has a MDP of about 30°C to about 45°C, preferably less than about 40°C, preferably less than about 35°C. The IV is about 68 to  
15 77, preferably from about 70 to 75.

Such an oil possesses an unusually high oxidative stability of from about 300 AOM hours to about 500 AOM hours, preferably from about 400 hours to about 500 hours, more preferably a minimum of about 425 hours.

20 Such an oil possesses a stearic acid content of about 5% to about 15%, a saturated fatty acid content of about 8% to about 20% and a *trans*-fatty acid content of about 20% to about 45%, preferably from about 25% to about 40%, more preferably from about 27% to about 32%.  
25 The total C18:1 content is from about 78% to about 88%, preferably from about 80% to about 85%.

In a fourth embodiment, a starting canola oil has been hydrogenated and fractionated to obtain an oil that has a MDP of less than about 20°C, preferably less than  
30 about 18°C. The oil has an IV of about 75 to about 81, preferably from about 78 to about 80.

An oil of this embodiment possesses a low *trans*-fatty acid content of from about 20% to about 35%, preferably from about 25% to about 30%, more preferably  
35 about 30%. An oil of this embodiment also possesses a

- 10 -

low saturated fatty acid content. For example, the stearic acid content of such an oil is from about 3% to about 6%, preferably from about 4% to about 5%. The total saturated fatty acid content is typically less than  
5 about 10%, preferably less than about 9.5%, more preferably about 9% or less.

An oil of this embodiment possesses a total C18:1 fatty acid content of greater than about 85%, preferably greater than about 86%, more preferably greater than  
10 about 87%, and up to about 92%.

An oil of this embodiment possesses a very high oxidative stability. When measured by the AOM method, such an oil possesses an AOM value of from about 350 hours to about 550 hours, preferably from about 400 hours  
15 to about 550 hours, more preferably a minimum of about 450 AOM hours.

An oil of the latter two embodiments may be produced by hydrogenation of a canola oil extracted from *Brassica* seeds. Such seeds have a fatty acid profile  
20 comprising an oleic acid content of from about 80% to about 87%, a linoleic acid content of from about 2% to about 5% and an alpha-linolenic acid content of from about 1% to about 4%. *Brassica* seeds having such a fatty acid profile may be produced, for example, by canola  
25 lines that contain defects in both *fad2* genes of *Brassica*, i.e., delta-12 fatty acid desaturase genes. Lines having defects in both delta-12 fatty acid desaturase genes are described in U.S. Patent Application Serial No. 08/572,027, filed December 14, 1995, which is  
30 incorporated herein by reference.

An illustrative example of a *Brassica* line suitable for preparing a starting canola oil for the latter two embodiments is a line known as 6Q4275A-1-4 (ATCC Accession No. 97569), also referred to herein as  
35 6Q4275. Progeny of crosses between a first *Brassica* line

- 11 -

(such as 6Q4275) and an agronomically elite line are also suitable for producing such a starting canola oil, provided that the progeny possess the fatty acid profile of the first *Brassica* line and that the oil extracted from the progeny can be hydrogenated as disclosed herein. Means for making such crosses and producing progeny are known in the art. An example of a progeny line suitable for making the starting canola oil is 93GS34-179, a line derived from a cross of 6Q4275 X Cyclone. Line 93GS34-179 (also referred to herein as 93GS or 93GS34) retains the fatty acid composition of 6Q4275 and has desirable agronomic characteristics.

Applicants have made a deposit of seeds of the *Brassica* lines indicated in Table 1 with the American Type Culture Collection (ATCC), Rockville, Maryland 20853 U.S.A. The seeds deposited with the ATCC are taken from the same deposit maintained by Cargill, Incorporated, Wayzata, Minnesota, since prior to the filing date of this application. These deposits will be maintained upon issuance of a patent without restriction in the ATCC depository, which is a public depository, for a period of 30 years, or 5 years after the most recent request, or for the effective life of the patent, whichever is longer, and will be replaced if the deposit becomes non-viable during that period.

TABLE 1

<u>Line</u>	<u>ATCC Deposit No.</u>	<u>Deposit Date</u>
IMC-130	75446	April 16, 1993
6Q4275A-1-4	97569	May 10, 1996

Other canola varieties suitable for preparing an oil of the invention may be obtained from progeny of the above-identified lines by known canola breeding methods including, but not limited to, outcrossing, backcrossing, recurrent selection, microspore culture and genetic transformation. Progeny are selected that retain the

- 12 -

genetic loci conferring the fatty acid profile and oil quality characteristics of the parent due to heritable genetic change that is present in the parent.

Varieties such as IMC-01 and IMC-129 are not  
5 useful in practicing the invention because such varieties do not produce a seed oil useful in developing a partially hydrogenated oil having the superior oil quality characteristics of the partially hydrogenated oils disclosed herein.

10 A method according to the invention comprises hydrogenation of a refined, bleached (RB) rapeseed oil under mild reaction conditions. A nickel catalyst typically is used to promote hydrogenation. A suitable catalyst has a high linolenic selectivity and a low  
15 trans-isomerization selectivity in order to use lower reaction temperatures (e.g., 155°C). Lower reaction temperatures permit hydrogenation of polyunsaturates in the oil while minimizing the formation of trans and saturated fatty acids. A suitable reaction temperature  
20 is from about 90°C to about 180°C, preferably from about 140°C to about 160°C. A high linoleic selectivity is also desirable in the catalyst.

Illustrative examples of suitable catalysts include Nysosel-545 and Nysosel-655 nickel catalysts  
25 (Engelhard Corporation, Jackson, MS). A suitable catalyst concentration is about 0.13 wt%. At this concentration, glucosinolates and other sulfur-containing compounds inherent in canola oil do not significantly interfere with the hydrogenation reaction. Hoffman, G.,  
30 The Chemistry and Technology of Edible Oils and Fats and High Fat Products, Academic Press, London, pp. 206-217 (1989).

In some embodiments, the hydrogenated material is fractionated to obtain a liquid oil fraction having a low  
35 trans-fatty acid content and a low saturated fatty acid

- 13 -

content. The unfractionated product is separated after hydrogenation into a solid fraction and a liquid canola oil fraction by techniques known in the art, e.g., plate and frame filtration, dry fractionation, or pressure  
5 filtration. Dry fractionation procedures may be used to separate the liquid and solid fractions of partially hydrogenated oils, e.g., a partially hydrogenated oil is crystallized at 21°C for 15 hours, centrifuged, and the liquid is separated. Alternatively, the liquid from the  
10 crystallized mixture is separated by pressure or vacuum filtration. Pressure filtration typically uses an inert gas, e.g., N<sub>2</sub> from about 14.7 psi to about 300 psi (101.3 kPa to 2067.9 kPa). See, e.g., EP 262 113, WO95/04123, and WO95/26391. Liquid yields tend to be higher with  
15 pressure filtration. In addition, a combination of the above procedures can be used to separate the liquid and solid fractions.

The hydrogenated and hydrogenated/fractionated liquid canola oils disclosed herein advantageously have a  
20 lower trans-fatty acid content compared to high oxidative stability soybean oils and cottonseed/soybean oil blends. Such liquid canola oils can have 30-40% less trans-fatty acids compared to the trans-fatty acid content of such soybean and soybean/cottonseed oils. Moreover, the MDP  
25 of such hydrogenated and fractionated canola oils can be more than 5°C lower than commercially available high AOM soybean or soybean/ cottonseed oils, (10°C MDP versus 16°C MDP).

The partially hydrogenated canola oils disclosed  
30 herein unexpectedly have high AOM values, despite the fact that the total C18:3 content is generally greater than 0.1% by weight, typically ranging from about 0.2% to about 0.8% by weight for oils having an IV of about 68 to about 80. At a given AOM value, a higher total C18:3  
35 content, in combination with a low trans-fatty acid and

- 14 -

total saturated fatty acid content, is preferred for nutritional reasons. The canola oils disclosed herein achieve such a desired combination of properties.

Hydrogenated and hydrogenated/fractionated canola  
5 oils disclosed herein may comprise substantially all of a final product. If desired, such oils can have various compounds added to form a final product, e.g., stabilizers, flavorings, emulsifiers, anti-spattering agents, colorants and/or antioxidants. Addition of  
10 antioxidants to hydrogenated or hydrogenated/fractionated canola oils disclosed herein significantly increases oxidative stability.

Hydrogenated and hydrogenated/fractionated canola oils may be used in food applications, e.g., frying oils,  
15 margarines or spreads, coating agents or confectionary fats. In addition, such oils may be used in industrial applications, e.g., energy transfer agents and friction-reducing agents. Energy transfer fluids include hydraulic fluids and lubricants. Friction-reducing  
20 fluids include cutting fluids, processing oils, motor oils and annealing agents. The hydrogenated and hydrogenated/fractionated oils disclosed herein provide an extended useful life and increased storage stability because of their high oxidative stability. Viscosity is  
25 more easily controlled with such oils compared to vegetable oils having lower oxidative stability. Moreover, the oils disclosed herein are biodegradable, thereby providing environmental benefits. If desired, the oils disclosed herein may be blended or mixed with  
30 other oils to meet the performance characteristics desired in the final product.

The invention will be further understood with reference to the following illustrative embodiments, which are purely exemplary and should not be taken as



- 15 -

limiting the true scope of the present invention as described in the claims.

### EXAMPLES

In the following Examples, all parts and percentages are by weight and all temperatures are degrees Celsius, unless otherwise stated. Oxidative stability is measured without deodorizing the hydrogenated product and without adding antioxidants, unless otherwise indicated.

10

#### EXAMPLE 1

IMC-129 (a high oleic acid variety) and IMC-01 (a low  $\alpha$ -linolenic acid variety) were the parent lines crossed to generate IMC-130. IMC-01 is described in U.S. Patent application Serial No. 08/290,660, incorporated herein by reference. IMC-129 is described in U.S. Patent application Serial No. 08/416,497, incorporated herein by reference.

IMC-130 seed was crushed and refined, bleached deodorized oil was prepared by a pilot plant process as described in Example 1 of U.S. Patent application 08/425,108, incorporated herein by reference. Pilot plant processing of oils tends to reduce AOM hours, as pilot plant processing typically is much harsher on the oil than commercial processing.

The RBD IMC-130 oil, along with commercially available canola oils, was analyzed for fatty acid composition by gas chromatography. Table 2 provides data on the fatty acid profiles of IMC-130 oil compared to commercially available canola oils: IMC-129 (a high oleic acid oil), IMC-144 (an identity-preserved canola oil lacking the high oleic and low linolenic acid traits) and Brand A (a typical generic canola oil). The data demonstrate reduced levels of linoleic ( $C_{18:2}$ ),  $\alpha$ -linolenic ( $C_{18:3}$ ), and total polyunsaturated fatty acids for IMC-130.

- 16 -

TABLE 2

Fatty Acid Composition of  
Refined, Bleached and Deodorized Oils

5	Variety Polys*	Fatty Acid Composition (%)					Total
		C <sub>16:0</sub>	C <sub>18:0</sub>	C <sub>18:1</sub>	C <sub>18:2</sub>	C <sub>18:3</sub>	
10	IMC-130	3.6	2.9	76.2	10.3	3.4	13.7
	IMC-144	2.9	2.1	62.6	19.5	8.1	27.6
	IMC-129	3.9	2.0	78.8	7.7	3.9	11.6
	Brand A	3.8	2.0	60.9	19.9	9.1	28.0

\*Total polyunsaturated acids

IMC-130, IMC-144, IMC-01, and IMC-129 oils were  
15 evaluated for AOM hours under the methods outlined in the  
American Oil Chemists' Society (AOCS) Official Method Cd  
12-57 for *Fat Stability:Active Oxygen Method* (rev'd.  
1989). Each oil sample was prepared in duplicate.

As shown in Table 3, IMC-130 oil was found to have  
20 significantly higher AOM hours after similar pilot plant  
processing than other oils tested. The greater oxidative  
stability of IMC-130 oil compared to IMC-144 oil or IMC-  
01 oil can be attributed to a lower polyunsaturated fatty  
acid content. However, the greater oxidative stability  
25 of IMC-130 oil compared to IMC-129 oil cannot be  
attributed solely to fatty acid composition because IMC-  
130 oil and IMC-129 oil have similar fatty acid  
compositions. In fact, IMC-130 oil can have slightly  
higher levels of polyunsaturates (Table 2). These  
30 results indicate that oxidative stability is not solely  
related to fatty acid composition.

TABLE 3

AOM Hours of Pilot Plant Processed Canola Oils

35	IMC-144	IMC-01 (Low ALA)*	IMC-129 (High Oleic)	IMC-130 (Example 1)
	15-22	20-22	16	37-40

\*ALA =  $\alpha$ -linolenic acid

- 17 -

EXAMPLE 2

IMC-129 and IMC-130 seed were crushed and processed by commercial processing methods to form refined, bleached, deodorized canola oil as described in Example 5 of U.S. Application Serial No. 08/425,108, filed June 6, 1995, incorporated herein by reference.

Oxidative stability of each oil was determined by measuring the increase in Peroxide Value and in para-Anisidine Value generated under accelerated aging conditions using a modified Schaal oven test. The test oil (200 g) was placed in an 500 ml uncovered amber glass bottle with a 4.3 cm opening, and placed in a 60°C convection oven. One bottle was prepared for each evaluation. Results are found in Table 4 and Table 5.

The peroxide value was measured using the AOCS Official Method Cd 8b-90. Hydroperoxides generated from oxidation of the triacylglycerols were measured by the peroxide value. The peroxide value was expressed in terms of milliequivalents of peroxide per 1000 grams of sample (meq/Kg). Reduced development of hydroperoxides during storage was an indicator of improved oxidative stability.

The para-anisidine value was measured using the AOCS Official Method Cd 18-90. Aldehydes generated from the oxidation of the triacylglycerol was measured by the p-anisidine value. The p-anisidine value was 100 times the optical density measured at 350 nm in a 1 cm cell of a solution containing 1.00 g of the oil in 100 ml of a mixture of solvent and reagent according to the method referenced, and is absorbance/g. Reduced development of aldehydes during storage is an indicator of improved oxidative stability of the oil.

- 18 -

TABLE 4

Accelerated Aging - Oxidative Stability  
Increase in Peroxide Value, Milliequivalents per kg

	<u>Days in oven:</u>	<u>IMC-130</u>	<u>IMC-129</u>
5	3	0.9	0.7
	6	2.1	2.3
	9	12.6	14.9
	12	16.1	22.1
	15	24.5	29.7

10

TABLE 5

Accelerated Aging - Oxidative Stability  
Increase in para-Anisidine Value, Absorbance per g

	<u>Days in oven:</u>	<u>IMC-130</u>	<u>IMC-129</u>
	6	0.1	0.2
15	9	2.0	3.1
	12	4.8	6.9
	15	6.9	10.2

The IMC-130 deodorized oil was analyzed for fatty acid composition via gas chromatography. The percent fatty acids were  $C_{16:0}$  of 3.6%,  $C_{18:0}$  of 2.2%,  $C_{18:1}$  of 74.3%,  $C_{18:2}$  of 11.9%,  $C_{18:3}$  of 4.8% and total polyunsaturated of 16.7%. These data can be compared to the values for IMC-144, IMC-129 and Brand A oils as shown in Table 2. The data demonstrate that IMC-130 maintains reduced levels of linolenic acid ( $C_{18:2}$ ),  $\alpha$ -linolenic ( $C_{18:3}$ ), and total polyunsaturated fatty acids when compared to canola oils IMC-144 and Brand A.

Table 6 provides data on the AOM hours of the IMC-130 oil processed as described above (commercial processing), compared to IMC-129, IMC-144, and IMC-01. The IMC-130 oil was evaluated for AOM hours under the methods outlined in the American Oil Chemists' (AOCS) Official Method Cd 12-57 for Fat Stability: Active Oxygen Method (rev'd 1989). The higher AOM hours of IMC-130 reflects its greater oil stability. Each oil sample was prepared in duplicate.

- 19 -

TABLE 6

AOM Hours of Commercially Processed Canola Oils

5	IMC-144	IMC-01 (Low ALA)*	IMC-129 (High Oleic)	IMC-130 (Example 2)
	15-18	30	30	37.5

\*ALA =  $\alpha$ -linolenic acidEXAMPLE 3

10 Canola oil was extracted from seeds of IMC-01, IMC-130 and 6Q4275, using pilot plant procedures or commercial plant procedures.

15	<u>Oil</u>	<u>Process</u>
	RBD IMC-01	Commercial
	RB IMC-01	Commercial
	RB IMC-130	Commercial
	RBD 6Q4275	Pilot

Typical characteristics of starting IMC-01 oils, IMC-130 oil, and 6Q4275 oil are shown in Table 7.

- 20 -

TABLE 7

## Oil Characteristics

IMC-01:

Refined, Bleached & Refined, Bleached, Deodorized Oils	
5	Color, Lovibond, 5.25" 1.0 red max
	Peroxide Value, (meq/kg) 1.0 max
	Iodine Value 105.±5.0
	Flavor and Odor ≥8
	AOM Stability, (hours) 25±2

10 IMC-130:

Refined, Bleached Oil	
	Color, Lovibond, 5.25" 1.0 red max
	Peroxide Value, (meq/kg) 1.0 max
	Iodine Value 95.0±5.0
15	Flavor and Odor ≥8
	AOM Stability, (hours) 35±2

6Q4275:

Refined, Bleached, Deodorized Oil	
	Color, Lovibond, 5.25" 0.3 red
20	Peroxide Value, (meq/kg) 1.14
	Iodine Value 90.3±1.0
	Flavor and Odor 7.1
	AOM Stability, (hours) 55±2

400 g of canola oil and the indicated amount of

25 catalyst were added to a Parr model 4563 reactor (Moline, IL). After assembly of the reactor, the water lines and the hydrogen line, the controller (Parr model 4548) was set to the desired temperature, the agitation speed was set to 600 rpm, and the reactor was placed under house

30 vacuum (~13 cm Hg). Once the set temperature of about 155°C was reached, the vacuum was shut off, the reactor was pressurized with hydrogen to 30 or 45 psi pressure and released to flush the reactor. The H<sub>2</sub> purge was repeated three times and the final pressure for

35 hydrogenation was set as indicated in the Tables. Hydrogenation consumption was calculated by closing the

- 21 -

hydrogen valve to the reactor and recording the pressure drop of hydrogen from either 30 or 45 psi for a 5 minute interval. Hydrogenation reaction conditions for each reaction are shown in Table 8.

5           At the end of the hydrogenation reaction, the product was stirred for 10 minutes with 0.5 wt% Celite (bleaching earth) and filtered through a Buchner funnel using a Whatman #5 and GF/F filter paper and 2-3 mm of silica gel (enough to cover the filter paper). This  
10 method was shown to reduce the amount of nickel catalyst in the filtrate down to 0.2 ppm. If desired, a citric acid treatment can be used to further reduce the nickel down to <0.11 ppm. An aliquot of the filtrate was then analyzed for IV, fatty acid composition, and oxidative  
15 stability as described below.

The hydrogenated material was melted on a steam bath and homogenized. Samples were then placed in centrifuge tubes, balanced, sealed, and left in a water bath at 13°C for 15 hours. The following day, the tubes  
20 were taken out and centrifuged at 10,000 RPM (10,000xG) for 20 minutes in a Beckman J-21C centrifuge. The supernatant was decanted and labeled the liquid fraction. The pellet was melted by steam bath, poured into an appropriate container, and labeled the solid fraction.  
25 Each fraction was analyzed as described below.

*Trans*-fatty acid levels and IV values of the final hydrogenated products, liquid fractions and solid fractions were determined by gas liquid chromatography (GLC). The GLC method is described in AOCS Official  
30 Method Ce 1c-89 (1991). Schaal Oven Stability was calculated from peroxide values. The fatty acid composition, iodine values, and tocopherol content also were determined.

- 22 -

Each sample was tested at 110°C for oxidative stability using an Oxidative Stability Index instrument, Omnion, Inc., Rockland, MA. AOM hours were calculated using the OSI software according to the manufacturers  
5 instructions.

The Oxidative Stability Index instrument was used to determine the oxidative stability of oils and fats according to AOCS Official Method Cd 12b-92 (revised 1993). The method is an automated replacement for the  
10 Active Oxygen Method (AOM) procedure, AOCS Official Method Cd 12-57.

The N-545 catalyst (26% Ni, 5% inert support) at a concentration of 0.13 wt % worked satisfactorily. A reaction temperature of 155°C kept the average  
15 hydrogenation rate >2 psi/min with an increase in trans-fatty acid formation ranging between 21% to 35% (Tables 8 and 9). The reaction temperature and the trans content can be lowered further by choosing a catalyst having higher activity and higher linolenic acid and linoleic  
20 acid selectivity. A hydrogenation pressure of 45 psi gave the best consumption rate of hydrogen in the reaction.

The fatty acid composition, iodine values and oxidative stability of hydrogenated and hydrogenated  
25 /fractionated oils are shown in Table 9. For RB IMC-130 oil, the AOM value was 351 hours for the liquid fraction of reaction 2689-28-L. RBD 6Q4275 canola oil had an AOM value of 307 hours in the liquid fraction of reaction 2695-11-L. The results shown in Table 9 demonstrate that  
30 a high oxidative stability canola oil that is liquid at or below room temperature can be produced from a starting IMC-130 oil or a starting 6Q4275 oil.



TABLE 8  
Hydrogenation Reaction Conditions

Type of Oil	Sample No.	Catalyst (wt%)	Temperature (oC)	Hydrogenation Pressure (psi) <sup>a</sup>	Reaction Time (min)	Rate of Hydrogenation (psi/min)	Final IV <sup>b</sup>
RBD IMC-01	2671-94	N-545 (0.2%)	155	30	140	1.48	78.59
RB IMC-01	2689-07	N-545 (0.5%)	155	30	120	1.64	90.14
	2689-16	N-545 (0.06%)	155	45	90	4.77	78.83
	2689-18	N-545 (0.13%)	155	45	110	7.31	68.09
RB IMC-130	2689-28	N-545 (0.13%)	155	45	90	3.43	70.16
RBD 6Q4275	2695-08	N-545 (0.13%)	150, 155	45	149	1.86	66.58
	2695-11	N-545 (0.13%)	130, 155	45	150	1.43	79

a: Pounds per square inch in the Parr Reactor.

b: Iodine Values determined by AOCs Tg 1a-64 methodology.

TABLE 9  
Fatty Acid Composition, Iodine Values, & AOM hours of Canola Oils after Hydrogenation and Fractionation.

Type of Oil	Sample No.	C16:0	C18:0	Total C18:1	Total C18:2	Total C18:3	Total trans	% Sats	IV <sup>c</sup>	AOM (hrs) <sup>d</sup>
RBD IMC-01	Control	3.97	2.46	66.32	21.83	2.14	0.29	10.77	101.5	24.40
	2671-94	3.96	8.31	80.14	4.47	0.55	25.94	—	78.86	108.28
	2689-07	4.03	4.58	73.08	14.13	0.73	8.55	—	90.14	22.40
	2689-16-F	4.04	10.43	75.45	7.05	0.35	22.51	15.82	78.83	42.30
	2689-16-L	3.70	7.22	77.49	7.35	0.34	21.51	12.12	81.08	69.90
RB IMC-130	2695-16-S	4.15	12.05	73.93	6.80	0.40	23.45	17.66	76.55	30.53
	2689-18	4.04	15.73	76.00	0.70	0.38	34.21	—	68.09	187.00
	Control	3.78	2.75	74.09	11.50	4.34	0.36	7.91	96.22	33.10
RB IMC-130	2689-28-F	3.83	13.53	77.36	1.14	0.37	31.92	19.04	70.16	327.20
	2689-28-L	3.17	8.70	83.61	1.16	0.46	30.94	13.28	75.86	351.00
	2689-28-S	4.09	15.36	75.02	0.95	0.41	32.19	21.24	67.88	287.59
	Control	3.44	1.92	84.08	3.39	4.02	0.64	6.49	90.29	56.91
RBD 6Q4275	2695-08-F	3.59	16.79	76.07	0.59	0.77	49.99	—	66.58	423.50
	2695-11-F	3.45	5.60	87.00	1.22	0.30	27.25	10.23	79.79	318.11
	2695-11-L	3.03	3.24	89.45	1.22	0.30	25.25	7.26	80.11	307.31
	2695-11-S	4.09	8.79	82.76	1.12	0.46	29.64	14.32	74.00	224.45

a: F refers to the hydrogenated product; S refers to the solid fraction; L refers to the liquid after dry fractionation/centrifugation at 1

b: The fatty acid composition determined by AOCS method Ce 1c-89 methodology.

c: IV, determined by AOCS method Ce 1c-89.

d: AOM hours as calculated from Oil Stability Index values.

- 25 -

EXAMPLE 4

The RBD 6Q4275 canola oil used in this Example was seven months old and had a PV of 1.67 meq/kg. Water washing and Celite treatment were carried out on the RBD 5 6Q4275 oil to remove citric acid. The 6Q4275 oil was extracted 3 times with 20% (v/v) water to oil. After extraction, the oil was mixed for 10 minutes with 0.5% Celite and filtered through glass membrane filter paper that was layered with a thin coat of silica gel. The 10 Celite addition and filtration procedure was repeated two more times to remove any polar contaminants.

450 g of RB IMC-130 or RBD 6Q4275 canola oil was placed in the Parr reactor. The agitation speed of the stirring motor was set to 600 rpm, and the temperature 15 was increased to 155°C. The reactor was placed under vacuum (2 mm of Hg) for 30 minutes with a pump and dry ice/isopropyl alcohol trap. This process removed any moisture and volatiles trapped in the oil. After 30 minutes, the oil was cooled to 35°C, the negative 20 pressure from the vacuum was equilibrated to atmospheric pressure, the reactor top removed and 0.13 wt % of N-545 catalyst was added to the oil. The reactor was reassembled and pressurized/purged three times with hydrogen to 35 psi. The reaction was heated to 155°C and 25 the hydrogen pressure was equilibrated at 45 psi. Hydrogen usage rate was calculated by closing the hydrogen valve to the reactor and recording the pressure drop of hydrogen from 45 psi for a 5 minute interval. After completing the hydrogenation, the samples were 30 treated with Celite and filtered through silica gel as described in Example 3. The reaction times, hydrogenation pressures and other reaction conditions are shown in Table 10.

IV and trans-fatty acid contents of hydrogenated 35 and hydrogenated/fractionated products were determined by

- 26 -

GLC as described in Example 3. Oxidative stability and fatty acid composition were determined as described in Example 3. The winterizing/centrifugation fractionation procedure was the same as in Example 3, except that the bath temperature was set at 21°C and centrifugation was carried out for 25 minutes.

Table 11 summarizes the results for hydrogenated and hydrogenated/fractionated IMC-130 canola oil. The IV ranged from about 66-76; the trans-fatty acid content was between 26% to 29%. The saturated fatty acid content for the liquid fraction was less than 14%.

The results for hydrogenated and hydrogenated/fractionated 6Q4275 oil samples are shown in Table 12. 6Q4275 samples had very high oxidative stability values, despite the fact that the starting oil was prepared by pilot plant processing, required removal of citric acid before hydrogenation and had a high initial PV. For example, the liquid fraction from sample 62 had 392 AOM hours, an IV of about 79 and a trans-fatty acid content of about 33%. An RB starting oil prepared by commercial processing and having a lower initial PV results in a hydrogenated/fractionated oil having an oxidative stability of up to 600 AOM hours.

Hydrogenated 6Q4275 and IMC-130 oils had high oxidative stability values even though the total C18:3 fatty acid content was greater than 0.2%. In contrast, known partially hydrogenated canola oils typically have less than 0.2% total C18:3 at correspondingly high oxidative stability values.

Characteristics of the liquid fraction of 2 hydrogenated IMC-130 oil samples are shown in Table 13. Both oil samples had a lower trans-fatty acid content compared to commercially available soybean and soybean/cottonseed oils of similar oxidative stability. The 65A-L oil (Table 13) had a superior flavor score,

- 27 -

lower color score, lower SFI and lower MDP compared to commercially available soybean and cottonseed/soybean oils of similar oxidative stability. 6Q4275 oils also have superior properties compared to commercially  
5 available cottonseed/soybean oils of similar oxidative stability.

- 28 -

TABLE 10  
HYDROGENATION REACTION CONDITIONS

Type of Oil	Reaction No.	Reaction Time (min)	Rate of Hydrogenation (psi/min)	Total Hydrogenation Consumption (psi)	Final IV
RB IMC-130	59A	118	4.44	524.3	70.14
	62A	125	3.98	497.5	70.01
RBD 6Q4275	51	80	5.56	444.8	72.26
	56	88	4.48	394.5	71.04
	62	77	4.97	382.5	73.81

TABLE 11

Fatty Acid Composition, Iodine Values, &amp; AOM hours of Hydrogenated IMC-130 Canola Oil

Sample	C16:0	C18:0	Total C18:1	Total C18:2	Total C18:3	Total trans	% sats.	IV	AOM (hrs)	MDP ( C)
Control	3.53	2.48	74.73	11.17	4.61	0.15	7.48	97.29	28.20	--
59A-F	3.59	14.03	76.32	1.70	0.33	27.52	19.28	70.14	267.11	34.6
59A-S	3.86	16.93	73.50	1.57	0.29	27.83	22.54	67.33	122.21	--
59A-L	3.15	9.03	82.11	1.77	0.32	26.53	13.56	75.28	336.89	17.7
62A-F	3.59	13.97	76.57	1.43	0.39	28.70	19.23	70.01	287.44	39.0
62A-S	3.84	16.87	73.25	1.25	0.35	29.09	22.49	66.67	156.39	--
62A-L	3.09	8.27	83.29	1.74	0.36	27.41	12.73	76.35	345.97	15.3

TABLE 12

Fatty Acid Composition, Iodine Values, &amp; AOM hours of Hydrogenated 6Q4275 Canola Oil

Sample	C16:0	C18:0	Total C18:1	Total C18:2	Total C18:3	Total trans	% sats.	IV	AOM(hrs)	MDP ( C)
Control	3.41	1.69	83.97	3.47	4.08	0.44	6.23	90.86	55.58	---
51-F	3.49	12.76	79.87	0.98	0.53	40.69	17.53	72.26	418.17	---
51-S	3.66	15.03	76.58	0.83	0.53	40.75	20.05	69.12	385.47	---
51-L	2.90	5.47	87.11	0.94	0.54	37.67	9.37	78.56	385.10	---
56-F	3.55	14.29	78.97	0.71	0.59	45.96	19.09	71.04	410.03	44.2
56-S	3.58	14.84	76.89	0.71	0.60	45.87	19.71	69.27	364.87	---
56-L	2.67	5.05	88.55	0.77	0.61	43.06	8.63	79.61	401.21	17.6
62-F	3.45	10.09	81.84	0.98	0.44	35.54	14.77	73.81	405.79	32.9
62-S	3.77	13.79	77.60	0.97	0.40	37.36	18.95	69.98	386.41	---
62-L	2.96	4.73	87.39	0.99	0.43	33.24	8.68	78.68	392.01	17.0



- 31 -

EXAMPLE 5

The effect of antioxidants on oxidative stability was also tested. The non-hydrogenated oils of Example 3 were mixed with the antioxidants indicated in Table 14.

- 5 Samples were then tested for oxidative stability as described in Example 3. Flavor scores were determined by AOCS method Cg 2-83. A score of greater than 7 indicates a slight to bland flavor, and is a preferred oil quality.

- As shown in Table 14, the oxidative stability of  
10 non-hydrogenated IMC-130 oil increased up to 2-fold when antioxidants were added, yet maintained preferred flavor scores. Non-hydrogenated 6Q4275 oil increased 3-fold in oxidative stability and had an improved flavor score when antioxidant TBHQ was added. Hydrogenated and  
15 hydrogenated/fractionated IMC-130 and 6Q4275 oils also show significant increases in oxidative stability when antioxidants are added, while maintaining superior flavor scores.

- 32 -

**TABLE 13**

Characteristics of High Oxidative Stability IMC 130 Oil

Type of Oil				
Characteristics	IMC-130 65A-L	IMC-130 84-2	Durkex 500®	Durkex 500S®
5 C16:0	3.24	3.00	6.46	9.67
C18:0	9.20	8.50	4.39	3.92
Total C18:1	81.66	83.24	82.98	79.72
Total C18:2	2.23	1.18	2.88	3.00
Total C18:3	0.29	0.55	0.11	0.07
10 %trans	26.68	31.72	47.55	39.56
IV	75.61	75.63	76.76	74.26
Hydroxyl Value	7.5	----	12.1	----
Color (Gardner)	1-2	1-2	3	5
Color (Lovibond-red)	0.5	0.5	1.7	4.8
15 Flavor Score <sup>a</sup>	8	----	5.9	6.2
Solid Fat Index 10°	4.3	----	17.9	12.5
Solid Fat Index 21°C	0.4	----	0.1	0.3
Mettler Drop Pt. (°C)	10	----	16.06	16
Tocopherols (ppm)	680	780	620	230
20 AOM (hours) <sup>b</sup>	347.4	436.59	438.26	327.36

<sup>a</sup>Determined according to AOCS method Cg2-83.<sup>b</sup>Calculated from OSI value.<sup>c</sup>Hydrogenated soybean oil, Van den Bergh Foods, Lisle, IL<sup>d</sup>Hydrogenated soybean/cottonseed oil, Van den Bergh Foods

- 33 -

**TABLE 14**

Oxidative Stability and Flavor Scores of  
Non-Hydrogenated Oils Having Added Antioxidants

5

Type of Oil	Sample No.	Herbalox O (ppm)	Ascorbalox A (ppm)	Duralox (ppm)	TBHQ (hours)	AOM (hours)	Flavor Score
IMC-130	Control	---	---	---	---	47.37	8.5
	130-02	510	---	---	---	52.55	7.9
	130-03	502	222	---	---	61.03	7.5
	130-04	512	550	---	---	59.72	7.8
	130-05	---	540	---	---	55.97	7.1
	130-12	---	1,000	---	---	63.58	---
	130-16	---	---	505	---	66.99	8.6
	130-17	---	---	1,015	---	83.35	7.8
	130-18	---	---	1,515	---	105.39	7.7
6Q4275	Control	---	---	---	---	43.00	7.1
	6Q-01	---	---	---	175	137.00	8.6

**EXAMPLE 6** [This example is all new]

IMC-130 and 93GS34-179 seed were crushed and  
 10 processed by commercial processing methods to produce  
 refined, bleached and deodorized IMC-130 and refined and  
 bleached 93GS34-179. Typical profiles of these starting  
 oils are shown in Table 15.

- 34 -

Table 15  
Analysis of Starting Materials

Characteristics	RBD IMC-130	RB 93GS
Peroxide Value, meq/kg	0.24	1.21
Free Fatty Acids, %	0.04	0.16
Colour, 5 1/4" Lovibond	4.0Y 0.6R	70.0Y 2.8R
Iodine Value	96.9	90.6
Fatty Acid Composition, %		
C14:0	0.1	0.1
C16:0	4.0	3.3
C16:1	0.5	0.3
C18:0	2.4	2.1
C18:1	73.1	82.3
C18:2	11.7	4.6
C18:3	4.6	4.0
C20:0	0.8	0.7
C20:1	1.5	1.4
C20:2	0.1	0.0
C22:0	0.4	0.4
C22:1	0.1	0.0
C24:0	0.2	0.2
C24:1	0.2	0.1
Tocopherols, mg/100g		
Delta	7.0	
Gamma	36.0	
Alpha	21.1	
Sterols, mg/100g		
Brassicasterol	63.7	
Campesterol	217.5	
$\beta$ -Sitosterol	341.1	

Two samples of each oil were hydrogenated under  
the conditions described in Table 16. Generally, 230 kg  
of oil was loaded into a 300 liter reactor and heated to

- 35 -

160°C under vacuum. The vacuum was broken with nitrogen when the initiation temperature was reached and the appropriate amount of catalyst was then added. The reactor was then reevacuated and hydrogen gas sparging  
5 started in the vessel. Cooling water was used on the jacket to remove excess heat from the reaction exotherm to maintain an approximate gassing temperature of 160°C. The reactions were monitored by refractive index until the appropriate end point. At this point, the oil was  
10 cooled and the vacuum was broken on the vessel using nitrogen.

The individual samples of hydrogenated IMC-130 and 93GS oil were bleached and deodorized in the following manner. The oil was heated to 60-65°C and 0.1% TriSyl  
15 S627, 1.0% of Supreme 120 FF bleaching clay was added and mixed. Oil temperature was increased to 108-112°C under vacuum. After mixing for 20 minutes, the samples were cooled to 70-75°C and 1.0 kg of filter aid was added. The samples were filtered using a stainless steel filter  
20 press (T. Shriver & Co. Ltd.) Subsequently, the bleached oil was deodorized at 250°C for IMC-130 and 260°C for 93GS, using a Johnson-Loft packed tower continuous deodorizer.

The fatty acid profile and iodine values of the  
25 hydrogenated products was determined as described in Example 3. The results are reported in Table 17. The average oxidative stability for the two IMC-130 samples was about 386 AOM hours, whereas the average oxidative stability of the two 93GS samples was about 326 AOM  
30 hours. Using refined and bleached IMC-130 oil instead of refined, bleached and deodorized IMC-130 oil may further increase the oxidative stability of the final product.

Table 16  
Hydrogenation Reaction Conditions

Type of Oil	Sample No.	Catalyst (wt%)	Temperature (C)	Hydrogenation Pressure (PSI/kPa)	Reaction Time (min)	Rate of Hydrogenation (kPa/min)
RBD IMC-130	3275-50-3	N-655 (0.3%)	160	45/310	22.3	13.9
	3275-50-4	N-655 (0.3%)	160	45/310	22.7	13.7
RB 93GS	3275-50-7	N-655 (0.3%)	160	45/310	14.5	21.4
	3275-50-8	N-655 (0.3%)	160	45/310	15.5	20.0

- 37 -

Table 17  
Analysis of Hydrogenated Oil

		IMC-130		93GS	
5	Iodine Value <sup>a</sup>	72.89	72.82	75.80	74.87
	<u>Fatty Acid Composition, %</u>				
	C14:0	0.06	0.06	0.05	0.06
	C16:0	4.12	4.12	3.42	3.42
	C16:1	0.21	0.18	0.17	0.16
10	C17:0	0.07	0.06	0.06	0.06
	C18:0	13.62	12.23	11.24	11.89
	C18:1	77.02	78.09	80.38	79.85
	C18:2	1.63	1.86	1.59	1.71
	C18:3	1.36	0.54	1.42	1.13
15	C20:0	0.99	0.94	0.88	0.90
	C22:0	0.42	0.41	0.35	0.36
	C24:0	0.25	0.24	0.21	0.23
	C24:1	0.09	0.10	0.08	0.09
	% Saturated	19.36	18.1	16.26	16.96
20	Total Trans (%)	32.95	36.21	24.88	21.01
	AOM	407	365	336	315

<sup>a</sup>IV was calculated from the fatty acid composition.

- 38 -

To the extent not already indicated, it will be understood by those of ordinary skill in the art that any one of the various specific embodiments herein described and illustrated may be further modified to incorporate  
5 features shown in other of the specific embodiments.

The foregoing detailed description has been provided for a better understanding of the invention only and no unnecessary limitation should be understood therefrom as some modifications will be apparent to those  
10 skilled in the art without deviating from the spirit and scope of the appended claims.



- 39 -

WHAT IS CLAIMED IS:

1. A hydrogenated canola oil, said oil having an MDP of more than about 30°C, a *trans*-fatty acid content of about 36% or less, an IV of from about 68 to about 75  
5 and a minimum AOM value of about 280 hours in the absence of added antioxidants.
2. The oil of claim 1, wherein said minimum AOM value about 325 hours.
3. The oil of claim 1, wherein said *trans*-fatty  
10 acid content is about 31% or less.
4. A hydrogenated and fractionated canola oil, said oil having an MDP of less than about 20°C, a *trans*-fatty acid content of about 31% or less, an IV of from about 72 to about 77 and a minimum AOM value of about 290  
15 hours in the absence of added antioxidants.
5. The oil of claim 4, wherein said minimum AOM value about 330 hours.
6. A hydrogenated canola oil, said oil having an MDP of more than about 30°C, a *trans*-fatty acid content  
20 of about 36% or less, an IV of from about 68 to about 75 and a minimum AOM value of about 280 hours in the absence of added antioxidants, said hydrogenated oil produced from a starting oil extracted from *Brassicaceae* seeds having a fatty acid profile comprising an oleic acid  
25 content of about 72% to about 80%, a linoleic acid content of about 5% to about 12% and an  $\alpha$ -linolenic acid content of about 1% to about 5%.

- 40 -

7. The oil of claim 6, wherein said trans-fatty acid content is about 31% or less.

8. The oil of claim 6, wherein said fatty acid profile is controlled by heritable genetic change that is present in seeds designated IMC-130 and having ATCC accession number 75446.

9. The oil of claim 6, wherein said minimum AOM value is about 325 hours.

10. A hydrogenated canola oil, said oil having an MDP of more than about 30°C, a trans-fatty acid content of about 40% or less, an IV of from about 68 to about 77, a total C18:1 content of about 80% or greater and a minimum AOM value of about 300 hours in the absence of added antioxidants.

11. The oil of claim 10, wherein said minimum AOM value is about 425 hours.

12. A hydrogenated and fractionated canola oil, said oil having an MDP of less than about 20°C, a trans-fatty acid content of about 40% or less, an IV of from about 75 to about 81, a total C18:1 fatty acid content of about 86% or greater and a minimum AOM value of about 350 hours in the absence of added antioxidants.

13. The oil of claim 12, said oil having a total saturated fatty acid content of less than about 9.5%.

14. The oil of claim 12, wherein said AOM minimum value is about 450 hours.

- 41 -

15. A hydrogenated canola oil, said oil having an MDP of more than about 30°C, a trans-fatty acid content of about 40% or less, an IV of from about 68 to about 77, a total C18:1 fatty acid content of about 80% or greater  
5 and a minimum AOM value of about 300 hours in the absence of added antioxidants, said hydrogenated oil produced from a starting oil extracted from Brassicaceae seeds having a fatty acid profile comprising an oleic acid content of about 80% to about 87%, a linoleic acid  
10 content of about 2% to about 5% and an  $\alpha$ -linolenic acid content of about 1% to about 4%.

16. The oil of claim 15, wherein said Brassicaceae seeds possess defects in first and second forms of delta-12 fatty acid desaturase.

15 17. The oil of claim 15, said fatty acid profile controlled by heritable genetic change that is present in seeds designated 6Q4275A-1-4 and having ATCC accession number 97569.

18. A method of producing a canola oil,  
20 comprising the steps of:

(a) providing a starting refined, bleached non-hydrogenated canola oil, said oil having an oleic acid content of from about 72% to about 80%, a linoleic acid content of from about 5% to about 12% and an  $\alpha$ -linolenic  
25 acid content of from about 1% to about 5%; and

(b) hydrogenating said starting oil to an IV of from about 68 to about 75, said hydrogenated oil having an MDP of more than about 30°C, a trans-fatty acid content of about 36% or less and a minimum AOM value of  
30 about 280 hours in the absence of added antioxidants.

- 42 -

19. The method of claim 18, wherein said trans-fatty acid content is about 31% or less.

20. The method of claim 18, further comprising the step of separating said hydrogenated oil into a solid  
5 fraction and a liquid canola oil fraction, said liquid fraction having an MDP of less than about 20°C, a trans-fatty acid content of less than about 31%, an IV of from about 72 to about 77 and a minimum AOM value of about 290 hours in the absence of added antioxidants.

10 21. The method of claim 20, wherein said AOM minimum value is about 330 hours.

22. The method of claim 18, wherein said starting oil is extracted from *Brassicaceae* seeds designated IMC-130 and having ATCC accession number 75446.

15 23. A method of producing a canola oil, comprising the steps of:

(a) providing a starting refined, bleached non-hydrogenated canola oil, said oil having an oleic acid content of from about 80% to about 87%, a linoleic acid  
20 content of from about 2% to about 5% and an  $\alpha$ -linolenic acid content of from about 1% to about 4%; and

(b) hydrogenating said starting oil to an IV of from about 68 to about 77, said hydrogenated oil having an MDP of more than about 30°C, a trans-fatty acid  
25 content of about 40% or less and a minimum AOM value of about 300 hours in the absence of added antioxidants.

24. The method of claim 23, further comprising the step of separating said hydrogenated oil into a solid fraction and a liquid canola oil fraction, said liquid  
30 fraction having an MDP of less than about 20°C, a trans-

- 43 -

fatty acid content of about 40% or less, an IV of from about 75 to about 81, a total C18:1 fatty acid content of greater than about 85% or greater and a minimum AOM value of about 350 hours in the absence of added antioxidants.

5           25. The method of claim 24, wherein said liquid canola oil fraction has a total saturated fatty acid content of less than about 9.5%.

          26. The method of claim 24, wherein said AOM minimum value is about 450 hours.

10           27. The method of claim 23, wherein said starting oil is extracted from *Brassicaceae* seeds having defects in first and second forms of delta-12 fatty acid desaturase.

          28. The method of claim 23, wherein said starting  
15 oil is extracted from *Brassicaceae* seeds designated 6Q4275A-1-4 and having ATCC accession number 97569.

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/US97/09326

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : A23D 7/00

US CL : 426/606, 607

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 426/606, 607

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 92/03919 A (DEBONTE) 19 MARCH 1992, PAGES 24-27.	1-28
Y	WO 94/15478 A (ZIELINSKI) 21 JULY 1994, PAGE 3, LINES 27-32.	1-28
Y	UNICHEMA INTERNATIONAL, Hydrogenation of Canola Oil, March 1992, page 6.	1-28



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:	*T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*A* document defining the general state of the art which is not considered to be of particular relevance	*X*	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*E* earlier document published on or after the international filing date	*Y*	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G*	document member of the same patent family
*O* document referring to an oral disclosure, use, exhibition or other means		
*P* document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

05 AUGUST 1997

Date of mailing of the international search report

25 AUG 1997

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

CAROLYN PADEN

Telephone No. (703) 308-3294